

TECHNICAL SPECIFICATION: RECOILED WIRE

ALFA RB 55



Description of the product

Weldable, sustainable reinforcing steel featuring improved bonding and high ductility, low carbon contents, packaged in coils, hot rolled and cold stretched.

Range of dimensions

- Diameter: 6 – 16 mm

Packaging

Coils strapped in 4 positions

Coil weight:

- ~ 2500 kg
- ~ 3000 kg
- ~ 5000 kg

Coil dimensions:

- \varnothing int. 630 mm
- \varnothing est. 1100 ÷ 1200 mm
- height 800 ÷ 1000 mm

Labelling

Each coil is identified with a metal or paper plastic label containing the following information:

- Company logo
- Lot number
- Diameter
- Weight
- Steel grade
- Production date
- Standards references
- Certification logos
- QR Code

TECHNICAL SPECIFICATION: RECOILED WIRE

ALFA RB 55

Certifications

Each delivery is accompanied by the certificate 3.1 (standard UNI EN 10204)



CONFORMITY TO STANDARDS			
Country	Standard	Grade	Certifications
AUSTRIA	ONORM B 4707	B 550 B	✓

CHEMICAL COMPOSITION					
C % max	P % max	S % max	Cu % max	N % max	Ceq. Max
0.22	0.050	0.050	0.80	0.012	0.50
(0.24)	(0.055)	(0.055)	(0.85)	(0.014)	(0.52)

The figures in brackets refer to product analysis

MECHANICAL PROPERTIES							
Standard	Grade	Re N/mm ²	Rm N/mm ²	Rm/Re	Agt %	A5 %	A10 %
ONORM B 4707	B 550 B	≥ 550		≥ 1.08	≥ 5		

GEOMETRICAL CHARACTERISTICS				
∅ mm	8	10	12	≥ 14
Relative rib area fR	≥ 0.040	≥ 0.040	≥ 0.040	≥ 0.056